

ONE HIGHBAY. SET IT ON SITE.

MALMBERGS
BE BRIGHTER

Highbay 100–200W, 4000K, IP65 · Art. no. 9972098

TOP SALES ARGUMENTS

UP TO 190 LM/W

 **60° · 90° · 120°**

ADJUSTABLE BEAM ANGLE

Set by DIP switch: narrow beam for high ceilings and rack aisles, wide beam for lower, open halls.

 **100 · 150 · 200 W**

ADJUSTABLE POWER

Choose the light level on site, from 16 500 to 38 000 lm, instead of stocking extra variants.

 **190 lm/W**

HIGH EFFICIENCY

More light per watt and lower energy costs in large spaces that are lit for long hours.

 **100 000 h**

LONG LIFETIME

L80 B10: 80 % of the light output remains after 100 000 h, about 11 years in 24/7 use.

WHY IT PAYS OFF



FEWER SKUS

3 power levels and 3 beam angles in one article.



QUICK TO INSTALL

Hook included, with a pre-mounted 0.3 m cable.



ROBUST

IP65 · IK08 · black aluminium housing.



SERVICEABLE

LED module and driver can be replaced.



APPLICATIONS

Industrial premises, warehouses, exhibition halls.



DOCUMENTED

CE · RoHS · multilingual installation manual.



SWEDISH QUALITY

DEVELOPED IN SWEDEN – SHIPPED FROM KUMLA



OWN DEVELOPMENT

Specified by our product management in Sweden. Part of the Malmbergs Pro range.



D-MARKED

Nordic marking for limited surface temperature (EN 60598-2-24), e.g. for farms and workshops.



SINCE 1981

Listed since 1999. ISO 9001 and ISO 14001 certified.



SHIPPED FROM KUMLA

Direct supply from our central warehouse in Sweden.

TECHNICAL DATA

POWER 100 / 150 / 200 W

LUMINOUS FLUX 16 500–38 000 lm

EFFICACY up to 190 lm/W

BEAM ANGLE 60° / 90° / 120°

LIGHT 4000K · Ra≥80 · 3 SDCM

PROTECTION IP65 · IK08 · Class I

LIFETIME 100 000 h (L80 B10)

VOLTAGE 230V

DIMENSIONS 340x340x157 mm

CABLE 0.3 m H05RN-F 3G1.0

MOUNTING Hook included

ENERGY CLASS C (light source)