

HW Device connection socket E117

Order number: 7350096

Type: E117



The basics for a proper hollow wall installation

- With break-outs for cables and pipes
- Integrated management support for NYM cables
- Secure fixing of tubes

Dimensions

| | |
|-----------------------|------------|
| Depth | 61 - 61 mm |
| Diameter | 68 mm |
| Internal depth | 60 mm |
| Milling hole diameter | Ø 68 mm |

Environmental conditions

| | |
|---|--------|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 % |
| Max. rel. humidity at 40°C | 50 % |

Material

| | |
|-----------------|----|
| Socket material | PP |
|-----------------|----|

Properties

| | |
|---------------------------|--------|
| Can be lead sealed | - |
| Colour | Orange |
| Degree of protection (IP) | IP30 |
| Free of heavy metals | true |
| Halogen-free | - |
| Installation type | HW |
| PVC-free | true |
| Silicone-free | true |
| Stackable | - |
| Weather-resistant | - |

Technical features

| | |
|--|---------------------|
| Cable entry 3x1.5 ² | 4 |
| Cable entry 7x1.5 ² /5x2.5 ² | 2 |
| Design voltage | 400 V |
| max. cross section | 2,5 mm ² |
| Pipe entry M20 | 4 |
| Suitable for sheet thickness | 5-40 mm |

Certificates & standards

| | |
|----------------|--|
| CE | true |
| Glow wire test | 850 °C |
| REACH | true |
| RoHS | true |
| Standards | <ul style="list-style-type: none"> • DIN EN 60670-1 (VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22) |
| VDE | true |

Accessories

| | |
|---------------|------|
| Equipped with | None |
|---------------|------|