



HW Connection socket E119

Order number: 7350043

Type: E119

HW Abzweigdose E119. Durchmesser 74mm, Tiefe 50mm. Zubehör: Schraubdeckel. Farbe orange.

Dimensions

Depth	55 - 55 mm
Diameter	77 mm
Internal depth	54 mm
Milling hole diameter	Ø 74 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Lid material	PS
Socket material	PP

Properties

Can be lead sealed	-
Colour	Orange
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	HW
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Cable entry 3x1.5 ²	3
Cable entry 7x1.5 ² /5x2.5 ²	1
Design voltage	400 V
max. cross section	2,5 mm ²
Pipe entry M20/M25	4
Suitable for sheet thickness	5-40 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"> • DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None
---------------	------