

Industrial luminaire Inda LED, 33-63W, IP65, 4000K, 160lm/W

Item: 7298107

MALMBERGS



Product information

Robust, energy-efficient and easy-to-install industrial luminaire with high IP rating, ideal for really tough environments. Adjustable multi-mounts, connection spaces in both ends, pre-installed through-wiring. D-marked. Adjustable wattage in four increments with DIP switch. Suitable for use in most industrial areas, parking garages, warehouses etc.

Mounting

Key hole for surface mounting in ceiling. Integrated wire bracket with lockable hook for suspension on wire. Can also be mounted on rail.

Connection

Fast connection terminal block 5x2.5 mm², one on each end. Incl. through-wiring 5G2.5 mm². Cable inlet, Ø 20 mm, one on each end, with cable gland and rubber sealing in both ends.

Description

Grey body made of polycarbonate, opal diffuser made of polycarbonate. Incl. LED module and driver.

No. of drivers per MCB

B10 – 20 pc

B16 – 32 pc

C10 – 34 pc

C16 – 54 pc

Industrial luminaire Inda LED, 33-63W, IP65, 4000K, 160lm/W

Item: 7298107

MALMBERGS

<iframe width="560" height="315"
src="https://www.youtube.com/embed/coaBc9DkGfQ?si=TCp_XNgZj0PWgsp7"
title="YouTube video player" frameborder="0" allow="accelerometer;
autoplay; clipboard-write; encrypted-media; gyroscope;
picture-in-picture; web-share" allowfullscreen></iframe>

Specifications

Beam angle	120°
Brand	Malmbergs Pro
Colour	Grey
Colour consistency	3 SDCM
Colour rendering index (CRI)	Ra80
Colour temperature	4000K
Description	Without sensor
Dimmable	No
Dims (LxWxH)	1500x80x74 mm
Efficiency	160lm/W
Impact protection	IK08
IP rating	IP65
Lifetime	100 000 hrs (L80 B10)
Luminous flux	5600-10080 lm
Power	33-63W
Weight	1,8 kg
Voltage	230V