

# Industrial Luminaire Inda LED, 25-45W, IP65, 4000K, 160lm/W

Item: 7298105

**MALMBERGS**



## Product information

Robust, energy-efficient and easy-to-install industrial luminaire with high IP rating, ideal for really tough environments. Adjustable multi-mounts, connection spaces in both ends, pre-installed through-wiring. D-marked. Adjustable wattage in four increments with DIP switch. Suitable for use in most industrial areas, parking garages, warehouses etc.

### Mounting

Key hole for surface mounting in ceiling. Integrated wire bracket with lockable hook for suspension on wire. Can also be mounted on rail.

### Connection

Fast connection terminal block 5x2.5 mm<sup>2</sup>, one on each end. Incl. through-wiring 5G2.5 mm<sup>2</sup>. Cable inlet, Ø 20 mm, one on each end, with cable gland and rubber sealing in both ends.

### Description

Grey body made of polycarbonate, opal diffuser made of polycarbonate. Incl. LED module and driver.

### No. of drivers per MCB

B10 – 20 pc

B16 – 32 pc

C10 – 34 pc

C16 – 54 pc

# Industrial Luminaire Inda LED, 25-45W, IP65, 4000K, 160lm

Item: 7298105

**MALMBERGS**

<iframe width="560" height="315"  
src="https://www.youtube.com/embed/coaBc9DkGfQ?si=TCp\_XNgZj0PWgsp7"  
title="YouTube video player" frameborder="0" allow="accelerometer;  
autoplay; clipboard-write; encrypted-media; gyroscope;  
picture-in-picture; web-share" allowfullscreen></iframe>

## Specifications

Beam angle	120°
Brand	Malmbergs Pro
Colour	Grey
Colour consistency	3 SDCM
Colour rendering index (CRI)	Ra80
Colour temperature	4000K
Description	Without sensor
Dimmable	No
Dims (LxWxH)	1200x80x74 mm
Efficiency	160lm/W
Impact protection	IK08
IP rating	IP65
Lifetime	100 000 hrs (L80 B10)
Luminous flux	4000-7200 lm
Power	25-45W
Weight	1,5 kg
Voltage	230V